





Li-ion Battery Power, Portable Evacuation







Applied on F1B,2F0B/2F0BR,2F1B/2F1BR Available separately





Available separately









## **Product Features**




Li-ion battery powered



Overhead vacuum gauge



Anti-dumping oil leakage



Built-in solenoid valve

## **Technical Data**

Technical Data					4480031		
Model	F1B	2F0B	2F0BR	2F1B	2F1BR	F2BR	2F2BR
Voltage							

Model	F1B	2F0B	2F0BR	2F1B	2F1BR	F2BR	2F2BR	
Voltage	DC18V(AEG/ RIDGID interface)							
Ultimate Vacuum	150microns	15microns	15microns	15microns	15microns	150microns	15microns	
Input Power	1/4HP	1/4HP	1/4HP	1/4HP	1/4HP	1/3HP	1/2HP	
Flow Rate (Max.)	1.5CFM 42 L/min	1.5CFM 42 L/min	1.5CFM 42 L/min	2.5CFM 71 L/min	2.5CFM 71 L/min	5CFM 142 L/min	5CFM 142 L/min	
Oil Capacity	200ml	280ml	280ml	280ml	280ml	580ml	450ml	
Weight	4.5kg	5.0kg	4.5kg	5.0kg	4.5kg	6.5kg	7.5kg	
Dimension	289x113x198		309x1	339x130x225				
Reference running time			45mins(4.0Ah	40mins(4.0AhLi-ion battery)				
Reference charging time			210mins(4.0Ah	210mins(4.0AhLi-ion battery)				
Remarks	Due to the strict transportation terms, we can not include any Li-ion battery, you can choose our battery adapters for use your local batteries.							
Packing	Carton 3pcs							



## **F Series Cordless Vacuum Pump**

**Product Description** 

**WIPCOOL** 

18V Li-ion battery, they can delivers the runtime to complete multiple jobs on one charge. Enabling up to 45-60 minutes of

There has 3 flow rate(1.5/2.5/5 CFM) and compatible with the new generation refrigerant(A2L) for your choice. Equiped with built-in solenoid valve and overhead vacuum meter as standard.

In addition, reinforced aluminum alloy oil tank, effective heat dissipation, resistance to chemical corrosion. Oil color and level

which can easily be compatible with the use of the above brand batteries