

VP633 ATEX RATED 6CFM VACUUM PUMP



SPECIFICATIONS PRODUCT:

FLOW RATE: 6CFM

ULTIMATE VACUUM AT INPUT PORTS: 15 MICRONS

FOR USE WITH: A3, A2L, AND A1 REFRIGERANTS

NOT FOR USE WITH: R-702, R-717

OIL CAPACITY: 237ML

OIL COMPATIBILITY: FIELDPIECE VACUUM PUMP OIL (HIGHLY REFINED AND OPTIMIZED FOR PROPER SEALING AND LUBRICATION)

FIELDPIECE PART NUMBERS: OIL8X3, OIL32, OIL128

OIL BACKLIGHT: BLUE LED

OIL DRAIN: BALL VALVE

PORT SIZES: (1) 1/4", (2) 3/8", (1) 1/2"

COMPRESSOR: ROTARY VANE, TWO STAGE

MOTOR: 1/2 HP AC

RPM: 2866 (VP633 ~ 50 HZ)

POWER SOURCE: 110/230 VAC SELECTABLE 50 HZ (VP633)

NOMINAL CURRENT DRAW: 5A @ 110 VAC, 2A @ 230 VAC (VP633)

NOMINAL POWER: 550W @ 110V, 460W @ 230V (VP633)

UNIT INGRESS PROTECTION RATING: IP20

DIMENSIONS: 201 MM X 296 MM X 406 MM

WEIGHT EMPTY: 15 KG

OPERATING ENVIRONMENT: 0°C TO 40°C

INCLUDED IN PACKAGE:

VP633 VACUUM PUMP

2X 237ML OIL